

LEDVANCE.NO

MULTI COLOUR
MULTI LUMEN
ONE SOLUTION

LEDVANCE




MULTI SELECT
YOUR BUSINESS
MADE EASY

ALWAYS THE RIGHT PRODUCT

THE MULTI SELECT LUMINAIRES

The perfect luminaire adapts to its environment. The ultra-long-life LED luminaires from the LEDVANCE MULTI SELECT range allow you to easily set the luminous flux (lm) and/or light colour on the driver or luminaire by hand. The variety of luminaire types stands for maximum flexibility, reduced stock levels and optimal lighting at all times, all with a five-year product guarantee. For more success in your daily business. Visit ledvance.com/multiselect for more information.

**SELECT THE LUMINOUS FLUX
AND/OR THE ...**



**... COLOUR TEMPERATURE
ON THE LUMINAIRE**








**MULTI LUMEN
SPECIAL
FEATURES**

- LED luminaires with variable luminous flux (lumen)
- Easy-to-set luminous flux via switch on the driver or luminaire before installation
- Practical solution for optimal illumination, e.g. for different ceiling heights



**MULTI COLOUR
SPECIAL
FEATURES**

- LED luminaires with up to three different colour temperatures (warm white, cold white, daylight white)
- Easy-to-set light colour via switch on the driver or luminaire on-site
- Adjust the light colour to specific requirements before installation

Example of products shown in this sales flyer:

84 functionalities
that would require

84 different
luminaires

» fit into
only

28 luminaires

At the flick of a switch – make the right choice

CHOOSE LEDVANCE!



BENEFITS FOR WHOLESALERS

- Leaner ranges with lower storage capacities
- Less time and effort for consultation

BENEFITS FOR INSTALLERS

- Always the right product choice
- Quick and practical solutions
- Flexible changes before or after installation



EFFICIENT AND VERSATILE SURFACE SQUARE AND CIRCULAR

- Highly versatile with multi colour (3 000/4 000/5 000 K) or multi lumen (3 500/2 500/1 500 lm), selectable on the luminaire
- Wall and ceiling luminaires
- Easy and quick installation



All product details

Product name	GTIN (EAN)	El.nr.	Replacement for	lm	W	lm/W	K	L70 ¹			L x W x H [mm] Ø x H [mm]	
SURFACE SQUARE AND CIRCULAR												
SURFACE SQUARE 330 3CCT 24W 3CCT IP44	4099854042034	3310303	1 x 26 W CFLP	2000	24	83	3000/4000/5000	50000	120		330 x 330 x 75	1
SURFACE SQUARE 350 3CCT 18W 3CCT IP44	4099854042072	3310308	1 x 26 W CFLP	1440	18	80	3000/4000/5000	50000	120		350 x 75	2
SURFACE CIRCULAR 500 PS 42W 830 IP44 PS	4099854042119	3316057	2 x 32 W CFLP	3500/2500/1500	42/30/19	83/78	3000	50000	120		500 x 105	3
SURFACE CIRCULAR 500 PS 42W 840 IP44 PS	4099854042133	3316058	2 x 32 W CFLP	3500/2500/1500	42/30/19	83/78	4000	50000	120		500 x 105	3

FLEXIBLE ALL-ROUND SPOT COMBO

- Colour temperature adjustment with multi colour (2 700/3 000/4 000 K), selectable on the spot
- Brightness adjustment with two lumen packages via switch on the driver
- Additional cover rings separately available in different colours



All product details

Product name	GTIN (EAN)	El.nr.	Replacement for	lm	W	lm/W	K	L70 ¹			L x W x H [mm] Ø x H [mm]	
SPOT COMBO												
SPOT COMBO FIX V 5.5W CPS 60DEG IP65 WT	4099854092701	3252693	40 W INCAND.	400/600	3.5/5.5	114/109	2700/3000/4000	50000	60		81.5 x 48	1
SPOT COMBO ADJUST V 5.5W CPS 60DEG IP65 WT	4099854092725	3252694	40 W INCAND.	400/600	3.5/5.5	114/109	2700/3000/4000	50000	60		81.5 x 48	2

PRACTICAL IN ANY ENVIRONMENT DAMP PROOF COMPACT GEN 2

- Highly versatile due to multi lumen function that allows two different lumen packages
- Easy installation as mounting brackets can be positioned freely on the luminaire
- Easy access to electrical terminal thanks to end caps with twist and lock mechanism



All product details

Product name	GTIN (EAN)	El.nr.	Replacement for	lm	W	lm/W	K	L70 ¹			L x W x H [mm] Ø x H [mm]	
DAMP PROOF COMPACT GEN 2												
DAMP PROOF COMPACT GEN 2 1200 V 33W 840 IP66 PS	4058075740877	3310218	2 x 36 W FL	3960/2600	33/21	123/120	4000	75000	120		1243 x 60 x 53	
DAMP PROOF COMPACT GEN 2 1500 V 50W 840 IP66 PS	4058075740891	3310219	2 x 58 W FL	6100/4200	50/34	123/122	4000	75000	120		1543 x 60 x 53	

¹ t[h]: L70/B50 @ 25 °C (T_a)/t[h]: L80/B10 @ 25 °C (T_a) | ² Refer to www.ledvance.com/guarantee for precise conditions

ABOUT LEDVANCE

With business activities in over 140 countries, LEDVANCE is one of the world's leading general lighting companies. Emerging from OSRAM's general lighting division, LEDVANCE's portfolio includes LED lamps and luminaires, intelligent lighting products, traditional lamps and renewable energy solutions.
#POWERTHROUGHLIGHT

LEDVANCE AS
Fornebuveien 5
1366 Lysaker
Norge

LEDVANCE

FUNCTIONAL CONVENIENCE PANEL COMFORT + COMPACT

- Highly versatile due to selectable lumen packages on the driver and/or two multi colour versions with 3 000/4 000 K
- Through-wiring possible with included connector box
- External driver for extended flexibility and easy installation



All product details

Product name	GTIN (EAN)	El.nr.	Replacement for	lm	W	lm/W	K	L80 ¹			L × W × H [mm] Ø × H [mm]	
PANEL COMFORT CR190												
PANEL COMFORT 600 UGR<19 CPS CR190 36W 930 940	4058075 694460	3004888	4 × 18 W FL	4200/4000/3600/3400	36/29.5	122/118/115/112	3000/4000	60000	90	—	595 × 595 × 35	1
PANEL COMFORT CR190 DALI												
PANEL COMFORT 600 UGR<19 DALI CS CR190 36W 930 940	4058075 694507	3004889	4 × 18 W FL	4200	36	118	3000/4000	60000	90	DALI-2/loT	595 × 595 × 35	1
PANEL COMFORT UGR19												
PANEL COMFORT 600 UGR<19 PS 28W 830 U19 PS	4099854 014604	3310243	4 × 18 W FL	3640/3250/2900	28/25/22	130	3000	70000	90	—	595 × 595 × 32	1
PANEL COMFORT 600 UGR<19 PS 28W 840 U19 PS	4099854 014628	3310244	4 × 18 W FL	3640/3250/2900	28/25/22	130	4000	70000	90	—	595 × 595 × 32	1
PANEL COMFORT 600 UGR<19 PS 33W 830 U19 PS	4099854 015090	3310238	4 × 18 W FL	4320/3900/3640	33/30/28	130	3000	70000	90	—	595 × 595 × 32	1
PANEL COMFORT 600 UGR<19 PS 33W 840 U19 PS	4099854 015113	3310251	4 × 18 W FL	4320/3900/3640	33/30/28	130	4000	70000	90	—	595 × 595 × 32	1
PANEL COMFORT 600 UGR<19 PS 33W 865 U19 PS	4099854 015137	-	4 × 18 W FL	4320/3900/3640	33/30/28	130	6500	70000	90	—	595 × 595 × 32	1
PANEL COMFORT 1200 UGR<19 PS 33W 830 U19 PS	4099854 004087	3310257	2 × 36 W FL	4320/3640/3120	33/28/24	130	3000	70000	90	—	1195 × 295 × 11	2
PANEL COMFORT 1200 UGR<19 PS 33W 840 U19 PS	4099854 004100	3310258	2 × 36 W FL	4320/3640/3120	33/28/24	130	4000	70000	90	—	1195 × 295 × 11	2
PANEL COMFORT												
PANEL COMFORT 600 PS 28W 830 PS	4099854 014192	3310239	4 × 18 W FL	3640/3250/2900	28/25/22	130	3000	70000	110	—	595 × 595 × 32	1
PANEL COMFORT 600 PS 28W 840 PS	4099854 014215	3310240	4 × 18 W FL	3640/3250/2900	28/25/22	130	4000	70000	110	—	595 × 595 × 32	1
PANEL COMFORT 600 PS 33W 830 PS	4099854 014864	3310237	4 × 18 W FL	4320/3900/3640	33/30/28	130	3000	70000	110	—	595 × 595 × 32	1
PANEL COMFORT 600 PS 33W 840 PS	4099854 014888	3310247	4 × 18 W FL	4320/3900/3640	33/30/28	130	4000	70000	110	—	595 × 595 × 32	1
PANEL COMFORT 600 PS 33W 865 PS	4099854 014901	-	4 × 18 W FL	4320/3900/3640	33/30/28	130	6500	70000	110	—	595 × 595 × 32	1
PANEL COMFORT 1200 PS 33W 830 PS	4099854 002731	3310255	2 × 36 W FL	4320/3640/3120	33/28/24	130	3000	70000	110	—	1195 × 295 × 11	2
PANEL COMFORT 1200 PS 33W 840 PS	4099854 003981	3310256	2 × 36 W FL	4320/3640/3120	33/28/24	130	4000	70000	110	—	1195 × 295 × 11	2
PANEL COMPACT												
PANEL COMPACT 600 V 35W 830 840 U19 PS	4099854 206535	3361458	4 × 18 W FL	3850/3300	35/30	110	3000/4000	50000	90	—	595 × 595 × 32	1
PANEL COMPACT 625 V 35W 830 840 U19 PS	4099854 206573	-	4 × 18 W FL	3850/3300	35/30	110	3000/4000	50000	90	—	620 × 620 × 32	1
PANEL COMPACT 600 V 35W 830 840 U19 DALI	4099854 206603	3361459	4 × 18 W FL	3850	35	110	3000/4000	50000	90	DALI2	595 × 595 × 32	1
PANEL COMPACT 625 V 35W 830 840 U19 DALI	4099854 206689	-	4 × 18 W FL	3850	35	110	3000/4000	50000	90	DALI2	620 × 620 × 32	1

¹t[h]: L70/B50 @ 25°C (T_A)/t[h]: L80/B10 @ 25°C (T_A) | ²All DALI luminaires support DALI-2 Energy Data (DALI part 252) and DALI-2 Diagnostic Data (DALI part 253).

³Refer to www.ledvance.com/guarantee for precise conditions

LEDVANCE.NO