

# PRODUCT DATASHEET

## ENDURA Style Disc Wall 8W

ENDURA STYLE DISC | Stainless steel wall-luminaire sensor optional



---

### Areas of application

- Building facades
- Entrance lighting
- Patios, balconies

---

### Product benefits

- Easy and quick installation
- Energy-efficient thanks to LED technology

---

### Product features

- Bright and functional outdoor LED luminaires
- Available with and without motion sensor
- Stainless steel housing
- Type of protection: IP44



TECHNICAL DATA

Electrical data

|                                                             |               |
|-------------------------------------------------------------|---------------|
| Nominal wattage                                             | 8.00 W        |
| Nominal voltage                                             | 220...240 V   |
| Mains frequency                                             | 50...60 Hz    |
| Nominal current                                             | 56.000 mA     |
| Max. number of luminaires per miniature circuit breaker B16 | 188           |
| Max. number of luminaires per miniature circuit breaker C10 | 186           |
| Max. number of luminaires per miniature circuit breaker C16 | 298           |
| Power factor $\lambda$                                      | $\geq 0.5$    |
| Total harmonic distortion                                   | < 20 %        |
| Protection class                                            | II            |
| Operating mode                                              | Mains voltage |

Photometrical data

|                                                |                           |
|------------------------------------------------|---------------------------|
| Luminous flux                                  | 370 lm                    |
| Total luminous flux of contained light sources | 850 lm                    |
| Luminous efficacy                              | 46 lm/W                   |
| Color temperature                              | 3000 K                    |
| Light color (designation)                      | Warm White                |
| Color rendering index Ra                       | $\geq 80$                 |
| Standard deviation of color matching           | $\leq 6$ sdc <sub>m</sub> |
| Photobiological safety group acc. to EN62778   | RG0                       |
| Photobiological safety group acc. to EN62471   | RG0                       |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 200.00 mm |
| Height         | 60.00 mm  |
| Product weight | 646.00 g  |

ENDURA STYLE DISC WALL ST

Materials & Colors

|                 |                    |
|-----------------|--------------------|
| Product color   | Steel              |
| Housing color   | Steel              |
| Body material   | Stainless steel    |
| Cover material  | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

### Application & Mounting

|                                        |                             |
|----------------------------------------|-----------------------------|
| Ambient temperature range              | -20...+40 °C                |
| Temperature range at storage           | -20...+80 °C                |
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |
| Type of protection                     | IP44                        |
| Protection class IK (shock resistance) | IK03                        |
| Dimmable                               | No                          |
| Mounting type                          | Surface                     |
| Application environment                | Outdoor                     |
| With light source                      | Yes                         |
| Replaceable light source               | No                          |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 25000 h <sup>1)</sup> |
| Number of switching cycles | 12500                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / UKCA       |
| Luminaire with limited surface temperature, "D sign" | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

## DOWNLOAD DATA

| Documents and certificates                                                       |                                        | Document name             |
|----------------------------------------------------------------------------------|----------------------------------------|---------------------------|
|  | User instruction / safety instructions | ENDURA STYLE DISC WALL    |
|  | Legal information                      | Safety insert G11219279   |
|  | Declarations of conformity             | EC_ENDURA STYLE DISC WALL |
|  | Declarations of conformity UKCA        | Fixed LUM                 |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854461453 | Folding box<br>1             | 207 mm x 72 mm x 207 mm              | 827.00 g     | 3.09 dm <sup>3</sup>  |
| 4099854461460 | Shipping box<br>4            | 302 mm x 225 mm x 235 mm             | 3664.00 g    | 15.97 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.