

# PRODUCT DATASHEET

## Tracklight Spot Cylinder GU10 Black

Tracklight Spot Cylinder | Tracklight spot with socket GU10



### Areas of application

- Kitchens, living rooms, children's rooms or home offices
- Entrance areas

### Product benefits

- Can be rotated and swiveled for optimum illumination
- Timeless elegant design
- Quick and easy lamp replacement
- High-quality materials

### Product features

- Customisable modular tracklight system




TECHNICAL DATA

Electrical data

|                  |             |
|------------------|-------------|
| Nominal voltage  | 220...240 V |
| Mains frequency  | 50...60 Hz  |
| Protection class | II          |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 140.00 mm |
| Width          | 55.00 mm  |
| Height         | 130.00 mm |
| Product weight | 270.00 g  |



Materials & Colors

|                 |        |
|-----------------|--------|
| Product color   | Black  |
| Housing color   | Black  |
| Body material   | Steel  |
| Mercury content | 0.0 mg |

Application & Mounting

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Type of protection        | IP20         |
| Dimmable                  | No           |
| Mounting type             | Surface      |
| Application environment   | Indoor       |
| With light source         | No           |
| Replaceable light source  | No           |

|                    |      |
|--------------------|------|
| Holder designation | GU10 |
|--------------------|------|

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

### Additional product data

|                       |   |
|-----------------------|---|
| Number of illuminants | 1 |
|-----------------------|---|

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                         |
|------------------------------------------------------------------------------------|----------------------------------------|---------------------------------------|
|  | User instruction / safety instructions | TRACKLIGHT SPOT MINICYLINDER_CYLINDER |
|  | Legal information                      | Safety insert G11219301               |
|  | Declarations of conformity             | TRACKLIGHT SPOT                       |
|  | Declarations of conformity UKCA        | Fixed LUM without EMC                 |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854455308 | Folding box<br>1             | 82 mm x 82 mm x 183 mm               | 365.00 g     | 1.23 dm <sup>3</sup> |
| 4099854455315 | Shipping box<br>4            | 178 mm x 178 mm x 198 mm             | 1460.00 g    | 6.27 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.