

# PRODUCT DATASHEET

## ENDURA Classic Spot Square Wall

Endura Classic Spot Square | Outdoor Endura Classic spot square socket GX53



### Areas of application

- Entrance lighting
- Patios, balconies
- Building facades

### Product benefits

- High flexibility in the choice of the light source thanks to GX53 base
- Easy and quick installation
- High-quality materials

### Product features

- Die-cast aluminum housing
- Adjustable luminaire head



TECHNICAL DATA

Electrical data


|                  |             |
|------------------|-------------|
| Nominal voltage  | 220...240 V |
| Mains frequency  | 50...60 Hz  |
| Protection class | I           |

Photometrical data

|                                 |   |
|---------------------------------|---|
| Flickering metric (Pst LM)      | - |
| Stroboscope effect metric (SVM) | - |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 100.00 mm |
| Width          | 170.00 mm |
| Height         | 90.00 mm  |
| Product weight | 420.00 g  |



ENDURA CLASSIC SPOT SQUARE  
WALL GX53

Materials & Colors

|                                            |                             |
|--------------------------------------------|-----------------------------|
| Product color                              | Black                       |
| Housing color                              | Black                       |
| Body material                              | Aluminum Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                      |
| Mercury content                            | 0.0 mg                      |

Application & Mounting

|                           |                             |
|---------------------------|-----------------------------|
| Ambient temperature range | -20...+40 °C                |
| Type of connection        | Terminal, 3-Pole (L, N, PE) |
| Type of protection        | IP44                        |
| Dimmable                  | No                          |
| Mounting type             | Surface                     |

|                          |         |
|--------------------------|---------|
| Application environment  | Outdoor |
| Adjustable               | Yes     |
| With light source        | No      |
| Replaceable light source | No      |
| Holder designation       | GX53    |

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

### Additional product data

|                       |   |
|-----------------------|---|
| Number of illuminants | 1 |
|-----------------------|---|

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                   |
|------------------------------------------------------------------------------------|----------------------------------------|---------------------------------|
|  | User instruction / safety instructions | ENDURA CLASSIC SPOT SQUARE WALL |
|  | Legal information                      | Legal insert I-Outdoor          |
|  | Declarations of conformity             | ENDURA CLASSIC SPOT SQUARE      |
|  | Declarations of conformity UKCA        | Fixed LUM without EMC           |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075763845 | Folding box<br>1             | 112 mm x 172 mm x 97 mm              | 481.00 g     | 1.87 dm <sup>3</sup>  |
| 4058075763852 | Shipping box<br>6            | 308 mm x 190 mm x 252 mm             | 3220.00 g    | 14.75 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.