

# PRODUCT DATASHEET

## Orbis Paris 400 mm 2XE27 Beige

Orbis Paris | Socketed ceiling luminaires with fabric ring



---

### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

---

### Product benefits

- Replaceable LED lamp
- Elegant design

---

### Product features

- Decorative domestic lighting
- Ceiling luminaire with socket
- Fabric material




TECHNICAL DATA

Electrical data

|                  |               |
|------------------|---------------|
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50...60 Hz    |
| Protection class | I             |
| Operating mode   | Mains voltage |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 400.00 mm |
| Height         | 105.00 mm |
| Product weight | 610.00 g  |



ORBIS PARIS

Materials & Colors

|                                            |                     |
|--------------------------------------------|---------------------|
| Product color                              | Beige               |
| Housing color                              | Beige               |
| Body material                              | Steel TC fabric PVC |
| Cover material                             | Polystyrene (PS)    |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C              |
| Mercury content                            | 0.0 mg              |

Application & Mounting

|                              |                             |
|------------------------------|-----------------------------|
| Ambient temperature range    | -20...+40 °C                |
| Temperature range at storage | -20...+80 °C                |
| Type of connection           | Terminal, 3-Pole (L, N, PE) |
| Type of protection           | IP20                        |
| Dimmable                     | No                          |
| Mounting type                | Surface                     |
| Application environment      | Indoor                      |
| With light source            | No                          |

|                          |    |
|--------------------------|----|
| Replaceable light source | No |
|--------------------------|----|

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name            |
|------------------------------------------------------------------------------------|----------------------------------------|--------------------------|
|    | User instruction / safety instructions | ORBIS                    |
|   | Legal information                      | Legal Insert             |
|  | Declarations of conformity             | ORBIS MADRID PARIS MILAN |
|  | Declarations of conformity UKCA        | ORBIS MADRID PARIS MILAN |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075832657 | Folding box<br>1             | 112 mm x 412 mm x 412 mm             | 984.00 g     | 19.01 dm <sup>3</sup> |
| 4058075832664 | Shipping box<br>4            | 426 mm x 426 mm x 475 mm             | 5065.00 g    | 86.20 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.