


PRODUCT DATASHEET LS AY P CSW P5 50

CONNECTORS FOR RGBW LED STRIPS IP00 GEN 2 | Connectors for RGBW LED Strips



Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	24 V
Nominal current	4440 mA

Dimensions & Weight



Length	83 mm
Cable length	50 mm
Width	13.7 mm
Height	4.3 mm
Cable cross-section, input side	0.5 mm ²
Cable cross-section, output side	0.5 mm ²
Product weight	7.6 g

Colors & materials

Product color	Transparent
Body material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20+55 °C		
Temperature range in operation	-20+55 °C		
Permitted rel. humidity during operation	055 %		

Additional product data

Product remark Av	Available from December 2024
-------------------	------------------------------

Certificates & Standards

Approval marks – approval	CE / UKCA / EAC
Standards	CE / UKCA
Type of protection	IP20

LOGISTICAL DATA

Temperature range at storage -20+80 °C
--

DOWNLOAD DATA

	Documents and certificates		Document name	
POF	Legal information		Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity		CE declaration - LS module	
POF	Declarations of conformity UKCA		UKCA declaration - LS module	
	Tender texts	Document name		
	Tender documents	CONNECTORS FOR RGBW LED STRIPS IP00 GEN 2 CSW P5 50-en		

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854359057	BAG 2	100 mm x 75 mm x 6 mm	16.20 g	0.05 dm ³
4099854359064	Shipping box 50	180 mm x 100 mm x 180 mm	480.00 g	3.24 dm ³
4099854359071	Shipping box 500	520 mm x 380 mm x 210 mm	5365.00 g	41.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.