

PRODUCT DATASHEET

LN UO DA 1200 P 27W 83040 WT

LINEAR ULTRA OUTPUT DALI GEN 2 | DALI surface luminaire with high luminous efficacy up to 150 lm/W

Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Indoor applications
- Industrial and commercial halls
- Public areas
- Corridors, stairwells, basements



Product benefits

- Highly versatile due to selectable CCT (Multi Color) in 3000K and 4000K
- DALI based light management system integrable into building management systems
- Integrated DALI-2 driver for extended functionalities
- SMD LEDs are moisture-proof and corrosion-proof thanks to tri-proof coating
- Energy savings up to 70 % (compared to luminaires that use fluorescent lamps)
- Robust structure with IK08
- Easy installation and versatile application

Product features

- DALI-2 certified
- DALI/Touch DIM® control signal
- Three-proof coating to improve the protection of the SMD LEDs



- Very high luminous efficacy: up to 150 lm/W
- Robust metal housing and PC diffuser
- Through wiring possible


TECHNICAL DATA

Electrical data


Nominal wattage	27.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	120 mA
Inrush current	9 A
Inrush current time T_{h50}	250 μ s
Max. number of luminaires per miniature circuit breaker B16	48
Max. number of luminaires per miniature circuit breaker C10	27
Max. number of luminaires per miniature circuit breaker C16	44
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	I
Operating mode	Integrated LED driver
Dimming interface	DALI-2

Photometrical data

Luminous flux	4050 lm / 3780 lm
Luminous efficacy	150 lm/W / 140 lm/W
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	< 3 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	110 °



LN UO DA 1200 P 27W CS WT




LN UO DA 1200 P 27W CS WT

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
27 W	4000 K	4050 lm	150 lm/W
27 W	3000 K	3780 lm	140 lm/W

Dimensions & Weight

Length	1168.00 mm
Width	65.00 mm
Height	74.00 mm
Product weight	1210.00 g



LN UO P 1200 27W CPS WT

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9003
Body material	Steel
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-40...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP20
Protection class IK (shock resistance)	IK08
Dimmable	Yes
Type of dimming	DALI2
Dimming range	1...100 %
Mounting type	Surface
Mounting location	Ceiling / Wall
Adjustable	No
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	88000 h ¹⁾
Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	248 mA
ECG - Output ripple current	< 5 %
Recommended control gear	LF-FSD037YA

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00055-V01.01-EN
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from September 2025
Added function	MULTI SELECT

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LINEAR ULTRA OUTPUT DALI GEN2
	Legal information	LISO Insert LINEAR ULTRA OUTPUT DALI
	Legal information	Safety Insert G11205497
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Legal Insert G11231526
	Declarations of conformity	LN UO DA
	Declarations of conformity UKCA	LN UO DA
	EU Data Act	DALI LED Driver and Luminaires
	EPD	ENVIRONMENTAL PRODUCT DECLARATION LINEAR ULTRA OUTPUT GEN 2

Photometric and lighting design files		Document name
	IES file (IES)	LN UO DA 1200 P 27W CS WT
	LDT file (Eulumdat)	LN UO DA 1200 P 27W CS WT
	UGR file (UGR table)	LN UO DA 1200 P 27W CS WT
	Light distribution curve type cone	LN UO DA 1200 P 27W CS WT
	Light distribution curve type polar	LN UO DA 1200 P 27W CS WT

CAD/BIM files		Document name
	BIM Revit 3D	Linear Ultra Output G2

Tender texts		Document name
	Tender documents	LINEAR ULTRA OUTPUT DALI GEN 2 DA 1200 P 27W CS WT-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075850392	Folding box 1	69 mm x 1,174 mm x 77 mm	1295.00 g	6.24 dm ³
4058075850408	Shipping box 6	1,184 mm x 225 mm x 170 mm	8425.00 g	45.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.