

PRODUCT DATASHEET

LED Spot Set CCT Recess IP44 Adjustable 4.9W CCT 36° White

LED Spot Set CCT Recess IP44 | Recess IP44 Front with CCT integrated LED



Areas of application

- Suitable for outdoor use
- Bathrooms
- Workshops, garages, covered outdoor storage areas

Product benefits

- Highly versatile due to selectable CCT
- Can be rotated and swiveled for optimum illumination
- Through-wiring possible with included connector box
- Easy mounting

Product features

- Recessed ceiling mounting
- Click-CCT version: color temperature adjustable in three steps by repeated switching
- Adjustable swivel angle
- With integrated LED module and driver
- Available with color temperature: 2,700 K, 4,000 K, 6,500 K
- Through wiring possible
- Type of protection, front side: IP44



TECHNICAL DATA

Electrical data


Nominal wattage	4.90 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	44.000 mA
Inrush current	6.1 A
Max. number of luminaires per miniature circuit breaker B16	29
Max. number of luminaires per miniature circuit breaker C10	18
Max. number of luminaires per miniature circuit breaker C16	29
Power factor λ	0.40
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	290 lm
Total luminous flux of contained light sources	420 lm
Luminous efficacy	59 lm/W
Color temperature	2700 K / 4000 K / 6500 K
Reference control setting of contained light source (Kelvin)	2700 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	80
Standard deviation of color matching	6 sdcn
Luminous intensity	570 cd
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	36 °

Dimensions & Weight

Diameter	88.00 mm
Height	40.00 mm
Product weight	208.00 g



SPOT SET 4.9W827 DIM IP44

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP44/IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	68 mm
Mounting depth	80 mm
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from October 2025
----------------	-----------------------------

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	Spotlights Adjustable CCT 3x4.9W
	Legal information	Legal insert
	Legal information	Safety insert G11222465
	Declarations of conformity	Spotlights IP44 and IP65
	Declarations of conformity UKCA	Spotlights IP44 and IP65

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854596063	Folding box 3	94 mm x 244 mm x 131 mm	701.00 g	3.00 dm ³
4099854596070	Shipping box 24	392 mm x 260 mm x 287 mm	6206.00 g	29.25 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.