

# PRODUCT DATASHEET Flex Motion Sensor Battery 2M 830

Battery Flex Strips Motion Sensor | Battery operated LED Strip with warm white light and motion sensor



## Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)

## Product benefits

- Easy and quick installation

## Product features

- Light color: Warm White
- Flexible, bendable LED strips

# TECHNICAL DATA

# Electrical data


Nominal wattage	3.60 W
Nominal voltage	6 V
Nominal current	600.000 mA
Power factor $\lambda$	> 0.50
Protection class	Ш

## Photometrical data

Luminous flux	150 lm
Luminous efficacy	41 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Beam angle	120°

# Dimensions & Weight

Length	2000.00 mm
Width	8.00 mm
Height	17.00 mm
Product weight	77.1 g



# Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

# **Application & Mounting**

Type of protection	IP20
Dimmable	No
Mounting type	Surface

With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
Number of switching cycles	10000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Sensor

Type of sensor	Motion	
Sensor technology	Passive infrared (PIR)	
Sensor detection angle	120 °	
Detection range of motion sensor	03 m	

# Certificates & Standards

Standards	CE / UKCA
Replaceable light source (EPREL)	Not replaceable

# **EQUIPMENT / ACCESSORIES**

- 4 x 1.5 AA batteries required (not in scope of delivery)

## Safety advice

 Do not connect the rope light to the supply while it is wound onto a reel. Do not use the lightstrip when covered or recessed into a surface. The string of lights may not be operated within the packaging. Do not open the lightstrip.

# DOWNLOAD DATA

Documents and certificates Document name	
struction / safety instructions Flex Motion Battery	PDF
formation Safety insert G11226671	PDF
tions of conformity FLEX MOTION SENSOR BATTERY	PDF
tions of conformity UKCA FLEX MOTION SENSOR BATTERY	PDF
tions of conformity FLEX MOTION SENSOR BATTERY	POF

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854448935	Folding box 1	34 mm x 101 mm x 142 mm	106.00 g	0.49 dm <sup>3</sup>
4099854448942	Shipping box 6	210 mm x 110 mm x 155 mm	743.00 g	3.58 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.