

PRODUCT DATASHEET

LED VALUE CLASS A 8 W/2700 K B22d

LED VALUE CLASSIC A | LED lamps, classic bulb shape



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- No "Blue Light" Hazard (according to IEC62778)
- Photobiological safety according to IEC 62778, risk group RG0
- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Color rendering index $R_a \geq 80$
- Not dimmable
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	220...240 V
Nominal current	62 mA
Type of current	AC
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz

Photometrical data

Luminous flux	806 lm
Luminous efficacy	100 lm/W
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827

Dimensions & Weight

Overall length	105.00 mm
Diameter	59.00 mm
Product weight	20.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Base (standard designation)	B22d
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0

Country-specific categorizations

Order reference	LVCLA60 8W/827
-----------------	----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	105.00 mm
Height	59.00 mm
Width	59.00 mm
EPREL ID	1403223
Model number	AC24708

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075383944	Folding box 3	182 mm x 62 mm x 117 mm	108.00 g	1.32 dm ³
4058075383951	Shipping box 24	506 mm x 192 mm x 130 mm	1105.00 g	12.63 dm ³
4099854254666	Shipping box 24	506 mm x 192 mm x 130 mm	889.00 g	12.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.