

## PRODUCT DATASHEET

### ST R63 40 36 ° 2.6 W/2700 K E27

LED STAR R63 | LED reflector lamps R63 with retrofit screw base



#### Areas of application

- Display cabinets and shop windows
- Museums, art galleries
- Hospitality
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Long lifetime of up to 15,000 h
- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of halogen lamps thanks to compact design
- Instant 100 % light, no warm-up time

#### Product features

- Professional LED alternative to halogen lamps
- Mercury-free lamps



TECHNICAL DATA

Electrical data

|                                        |             |
|----------------------------------------|-------------|
| Nominal wattage                        | 2.6 W       |
| Construction wattage                   | 2.60 W      |
| Nominal voltage                        | 220...240 V |
| Claimed equiv. conventional lamp power | 40 W        |
| Nominal current                        | 20 mA       |
| Type of current                        | AC          |
| Inrush current                         | 9.5 A       |
| Operating frequency                    | 50...60 Hz  |
| Mains frequency                        | 50...60 Hz  |
| Max. lamp number on MCB B10 A          | 300         |
| Max. lamp number on MCB B16 A          | 400         |
| Power factor $\lambda$                 | > 0.50      |

Photometrical data

|                                         |            |
|-----------------------------------------|------------|
| Luminous intensity                      | 398 cd     |
| Luminous flux                           | 210 lm     |
| Nominal useful luminous flux 90°        | 210 lm     |
| Luminous efficacy                       | 80 lm/W    |
| Lumen main.fact.at end of nom.life time | 0.70       |
| Light color (designation)               | Warm White |
| Color temperature                       | 2700 K     |
| Color rendering index Ra                | ≥80        |
| Light color                             | 827        |
| Standard deviation of color matching    | ≤6 sdcn    |
| Rated peak intensity                    | 398 cd     |
| Rated LLMF at 6,000 h                   | 0.80       |




Everlight 67-23ST KKE 2700K

Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 36 °     |
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

Dimensions & Weight



|                  |           |
|------------------|-----------|
| Overall length   | 102.00 mm |
| Diameter         | 63,0 mm   |
| Maximum diameter | 63 mm     |
| Product weight   | 102.00 g  |

Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 70 °C        |

Lifespan

|                                              |        |
|----------------------------------------------|--------|
| Number of switching cycles                   | 100000 |
| Lumen maintenance at end of service lifetime | 0.70   |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90 |

Additional product data

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | E27    |
| Mercury content             | 0.0 mg |
| Mercury-free                | Yes    |

|                |                                                                                                                                                                                                                                                                                                                                              |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|                                              |                 |
|----------------------------------------------|-----------------|
| Energy efficiency class                      | F <sup>1)</sup> |
| Energy consumption                           | 3.00 kWh/1000h  |
| Type of protection                           | IP20            |
| Standards                                    | CE / EAC / CB   |
| Photobiological safety group acc. to EN62778 | RG1             |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

### Country-specific categorizations

|                 |                  |
|-----------------|------------------|
| Order reference | LED6SR6340 2,6W/ |
|-----------------|------------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                     |                 |
|-----------------------------------------------------|-----------------|
| Light source cap-type (or other electric interface) | E27             |
| Correlated colour temperature type                  | SINGLE_VALUE    |
| Length                                              | 102.00 mm       |
| Height                                              | 63,0 mm         |
| Width                                               | 63,0 mm         |
| EPREL ID                                            | 1402945,1403197 |

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

### DOWNLOAD DATA

| Documents and certificates                                                         |                            | Document name |
|------------------------------------------------------------------------------------|----------------------------|---------------|
|  | Declarations of conformity | R63 R80 E27   |

| Documents and certificates                                                       |                                     | Document name                  |
|----------------------------------------------------------------------------------|-------------------------------------|--------------------------------|
|  | Declarations of conformity          | LED spot lamp R63 R80          |
|  | Declarations of conformity UKCA     | LED spot lamp R63 R80          |
| Photometric and lighting design files                                            |                                     | Document name                  |
|  | IES file (IES)                      | LEDPR6340 2.6W 827 230V GL E27 |
|  | LDT file (Eulumdat)                 | LEDPR6340 2.6W 827 230V GL E27 |
|  | Light distribution curve type polar | LEDPR6340 2.6W 827 230V GL E27 |
|  | Spectral power distribution         | Everlight 67-23ST KKE 2700K    |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075096967 | Blister<br>1                 | 65 mm x 140 mm x 120 mm              | 117.00 g     | 1.09 dm <sup>3</sup> |
| 4058075096974 | Shipping box<br>6            | 410 mm x 154 mm x 134 mm             | 883.00 g     | 8.46 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For further products and actual information concerning LED lamps see [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)
- For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.