

## PRODUCT DATASHEET

### DULUX T PLUS 26 W/830

OSRAM DULUX® T PLUS | CFLni, 3 tubes, with 2-pin base for CCG operation



#### Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industrial lighting

#### Product benefits

- Improved maintenance

#### Product features

- Good color rendering index
- Short and compact pin-base lamp with triple-turn tubes
- Single-ended two-pin plug-in GX24d base



TECHNICAL DATA


Electrical data

|                      |         |
|----------------------|---------|
| Nominal wattage      | 26 W    |
| Construction wattage | 27.90 W |
| Nominal voltage      | 105 V   |
| Nominal current      | 0.33 A  |

Photometrical data


|                           |                       |
|---------------------------|-----------------------|
| Luminous flux             | 1800 lm               |
| Luminous efficacy         | 65 lm/W <sup>1)</sup> |
| Light color (designation) | LUMILUX Warm White    |
| Color temperature         | 3000 K                |
| Color rendering index Ra  | ≥80                   |
| Light color               | 830                   |
| Rated LLMF at 2,000 h     | 0.85                  |
| Rated LLMF at 4,000 h     | 0.78                  |
| Rated LLMF at 6,000 h     | 0.76                  |
| Rated LLMF at 8,000 h     | 0.75                  |

1) At CCG



349617\_FL\_830

Dimensions & Weight



|                                             |           |
|---------------------------------------------|-----------|
| Overall length                              | 138.50 mm |
| Length with base excl. base pins/connection | 116,00 mm |
| Diameter                                    | 12.00 mm  |
| Tube diameter                               | 12 mm     |
| Product weight                              | 63.5 g    |

Temperatures & operating conditions

|                           |             |
|---------------------------|-------------|
| Ambient temperature range | -5...+40 °C |
|---------------------------|-------------|

Lifespan

|                                       |         |
|---------------------------------------|---------|
| Service life                          | 6500 h  |
| Rated lamp survival factor at 2,000 h | 0.99    |
| Rated lamp survival factor at 4,000 h | 0.99    |
| Rated lamp survival factor at 6,000 h | 0.95    |
| Rated lamp survival factor at 8,000 h | 0.81    |
| Lifespan B50                          | 10000 h |

Additional product data

|                             |         |
|-----------------------------|---------|
| Base (standard designation) | GX24d-3 |
| Mercury content             | 2.0 mg  |

Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | G               |
| Energy consumption      | 28.00 kWh/1000h |

### Country-specific categorizations

|                 |                      |
|-----------------|----------------------|
| ILCOS           | FSM-26/830-I-GX24d-3 |
| Order reference | DULUX T 26W/830      |

### Energy labelling regulation data acc EU 2019/2015

|                                                     |              |
|-----------------------------------------------------|--------------|
| Lighting technology used                            | CFLNI        |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | NMLS         |
| Light source cap-type (or other electric interface) | GX24d-3      |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope                                            | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Claim of equivalent power                           | No           |
| Length                                              | 138.50 mm    |
| Height                                              | 12.00 mm     |
| Width                                               | 12.00 mm     |
| Chromaticity coordinate x                           | 0,440        |
| Chromaticity coordinate y                           | 0,403        |
| Beam angle correspondence                           | SPHERE_360   |
| EPREL ID                                            | 546459       |
| Model number                                        | AC34234      |

### EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear
- Suitable for 0.22 A control gear only (DULUX T 18 W PLUS)

### Safety advice

- In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

## DOWNLOAD DATA

| Documents and certificates                                                        |                             | Document name                                                                   |
|-----------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------|
|   | Declarations of conformity  | EC Declaration of Conformity - 2021 9C1-4077884-EN-00 - DULUX T                 |
|   | Certificates                | EAC N RU D-DE.MU62.B.00933_20 06.03.2020-05.03.2025 Prommash Test - CFLpin      |
|   | Certificates                | EAC RU C-DE.HA46.B.01131_21 21.05.2021-20.05.2026 Expert Certification - CFLpin |
| Photometric and lighting design files                                             |                             | Document name                                                                   |
|  | Spectral power distribution | 349617_FL_830                                                                   |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300342061 | Folding box<br>1             | 45 mm x 48 mm x 142 mm               | 82.00 g      | 0.31 dm <sup>3</sup> |
| 4050300342078 | Shipping box<br>10           | 240 mm x 102 mm x 161 mm             | 874.00 g     | 3.94 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.