

## PRODUCT DATASHEET

### L 40W/865 G10Q

LUMILUX® T9 C | Circular fluorescent lamps 29 mm, with G10Q base



#### Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

#### Product benefits

- Excellent uniform illumination with no shadows

#### Product features

- Good color rendering index
- Single-ended round fluorescent lamp
- Dimmable



---

## TECHNICAL DATA

### Electrical data

|                      |         |
|----------------------|---------|
| Nominal wattage      | 40 W    |
| Construction wattage | 40.00 W |
| Nominal voltage      | 115 V   |

### Photometrical data

|                           |                       |
|---------------------------|-----------------------|
| Luminous flux             | 2750 lm               |
| Luminous efficacy         | 68 lm/W               |
| Light color (designation) | LUMILUX Cool Daylight |
| Color temperature         | 6500 K                |
| Color rendering index Ra  | 80...89               |
| Light color               | 865                   |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Overall length | 406.00 mm |
| Diameter       | 29.00 mm  |
| Product weight | 261.00 g  |

### Lifespan

|              |         |
|--------------|---------|
| Lifespan B50 | 13000 h |
|--------------|---------|

### Additional product data

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | G10q   |
| Mercury content             | 3.6 mg |

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | L 40W/865 C G10 |
|-----------------|-----------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                     |           |
|-----------------------------------------------------|-----------|
| Light source cap-type (or other electric interface) | G10q      |
| Length                                              | 406.00 mm |
| Height                                              | 29.00 mm  |
| Width                                               | 29.00 mm  |

---

## EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gears

---

### Safety advice

- In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

---

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075719026 | Sleeve<br>1                  | 421 mm x 411 mm x 38 mm              | 451.00 g     | 6.58 dm <sup>3</sup>  |
| 4058075719033 | Shipping box<br>12           | 452 mm x 436 mm x 431 mm             | 5865.00 g    | 84.94 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.