

PRODUCT DATASHEET LS AY SUP - CSW/P2/50

Connectors for LED Strips Superior Class | Connectors for LED Strips Superior Class

Areas of application

- General outdoor illumination





Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

| Nominal voltage | 25 V |
|-----------------|---------|
| Nominal current | 5000 mA |

Dimensions & Weight

| Length | 69.6 mm |
|---------------------------------|----------------------|
| Cable length | 50 mm |
| Width | 9.8 mm |
| Height | 5.7 mm |
| Cable cross-section, input side | 0.34 mm ² |
| Product weight | 6.00 g |

Colors & materials

| Product color White |
|---------------------|
|---------------------|

Temperatures & operating conditions

| Ambient temperature range | -35+75 °C |
|--------------------------------|-----------|
| Temperature range in operation | -35+75 °C |

Certificates & Standards

| Type of protection | IP00 |
|--------------------|------|
| | |

LOGISTICAL DATA

| Temperature range at storage -5+55 °C |
|---------------------------------------|
|---------------------------------------|

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075304475 | BAG 2 | 80 mm x 120 mm x 5 mm | 13.00 g | 0.05 dm ³ |
| 4058075304482 | Shipping box 100 | 180 mm x 100 mm x 180 mm | 729.00 g | 3.24 dm ³ |
| 4058075304499 | Shipping box 1,000 | 520 mm x 380 mm x 210 mm | 8057.00 g | 41.50 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.